TSI TOUCH

PCAP TOUCH SOLUTION 85" Integrated Touchscreen Display


TSI Touch's Projected Capacitive (PCAP) Metal Mesh solution for Samsung®'s 85" Q-series monitors allows for a highly accurate touchscreen experience. Through the use of advanced Metal Mesh sensor technology, coupled with a state of the art controller, our PCAP touch solution provides the interactive experience your end users expect, all while requiring little to no maintenance.

Our all-metal bezel construction, combined with anti-glare glass, adds considerable protection to the display, while also keeping your content crisp and bright.



| SPECIFICATION | DETAIL | | |
|------------------------------|--|--|--|
| Product Name | Touchscreen only | QB85R-B Integrated with Touchscreen | QM85R-B Integrated with Touchscreen |
| Part Number | TSI85NS156HPGZZ | TSI85PSWB6HPGZZ | TSI85PSWD6HPGZZ |
| Touchscreen Type | Projected Capacitive Metal Mesh on Anti-Glare | | |
| Number of Touch Points | 40 points simultaneous touch maximum | | |
| Touchscreen Interface | USB 2.0 Type A Male connector with 2 meter cable | | |
| Touchscreen Power | USB 5VDC Maximum 1.6W Peak | | |
| Touch Response Time | 5ms | | |
| Touch Accuracy | 0.53% of sensor area | | |
| Minimum Touch Object Size | 2.64% | | |
| Orientation Compatibility | Landscape, Portrait | | |
| Brightness (w/touchscreen) | N/A | 308 nit | 440 nit |
| Brightness (w/o touchscreen) | N/A | 350 nit | 500 nit |
| Display Resolution | 3840 x 2160 | | |
| Contrast Ratio | 4000:1 | | |
| Viewing Angle | 178/178 | | |

| Aspect Ratio | 16:9 | |
|--------------------------------------|---|--|
| Video Inputs | HDMI 2.0 (2) | |
| Audio Output | Stereo Mini Jack | |
| Operating System Compatability | Microsoft [®] Windows [®] , Samsung [®] SoC, Google [®] Chrome [®] , Android [®] , Ma- cOS [®] , and many popular Linux [®] Distributions - <i>HID Compliant</i> <i>Compatability</i> | |
| Display Power Supply | AC 100 - 240 V, 50/60 Hz | |
| Display Power Consumption | Typical: 217 Watts/Max: 308 Watts | |
| Operating Temperature | 0°~40° C | |
| Humidity | 10~80% Non-condensing | |
| Integrated Dimensions (W x H x D) | 77.36″ x 45.11″ x 2.55″ | |
| Viewable Area | 73.78″ x 41.53″ | |
| Integrated Display Weight | 197.6 lbs. | |
| Packaged Weight | 269.6 lbs. | |
| VESA Pattern | 600 x 400 mm | |
| Recommended Duty Cycle | QB: 16/7 \\\ QM: 24/7 | |
| Service and Support | 3 Year Repair & Return Warranty | |
| In the Box | Integrated Touchscreen Display, Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries | |



For more information, please visit www.tsitouch.com, email sales@tsitouch.com, or call 802-874-0123 Specifications and designs are subject to change without notice. Packaged weights are approximate.