

Phone: 802-874-0123 Fax: 703-991-8770

Email: sales@tsitouch.com

tsitouch.com

## **LG UHD Infrared Touch Screen Solutions**



### **Infrared Interactive Solution**

The TSItouch solution is Infrared (IR) based, allowing for a high accuracy interactive experience. The usage of IR technology allows for virtually any input to be detected (pen/stylus, user's fingers, palms, gloved fingers). The TSItouch overlay is a full steel chassis integrated with tempered cover glass, which increases durability and optical clarity, while protecting the display.



#### Multi-Touch Screen True multi-touch support for all major operating systems. 6, 10, 12, or 32 simultaneous touch point options are available



### Ultra-Fast Response Time

Allows for split second reactions between touch point and screen. Rapid and smooth touch response



### Superior Design

Full steel chassis combined with tempered glass provides additional protection to the LCD panel



## Branding Free

Branding/logo free, not to divert attention from your brand and messaging



# 24/7 Commercial Grade Display

Commercial grade display with around the clock functionality



## **Easy Integration**

Unrivaled simplicity makes installation easier and faster



## HID Compliant

Maximum compatibly with numerous operating systems, plug-and-play





### Customizable


Custom colors silk screening, and logos available



### **Solution Sizes Available**







Specification	49"	65"	79"
Display Compatible	49UX340C	65UX340C	79UX340C
Part Number	TSI49PLBWQ6ARZZ	TSI65PLCSQ6ARZZ	TSI79PLLMQ6ARZZ
Protective Glass	1/8" Anti-Reflective Cover Glass	3/16" Anti-Reflective Cover Glass	
Viewing Angle	178x178 degrees		
Audio Output	10W + 10W		
Touch Technology	IR G5		
Touch Points	6 Point		
Response Time	9ms		
Touch Accuracy	+/- 1.5mm (Over 99% Area)		
Interface	Type A USB		
Communication	USB 2.0		
Power Supply Mode	Single USB connection (5v, 1A)		
Duty Cycle	24/7		
Panel Technology	IPS		
Aspect Ratio	16:9		
Connectivity	(2) HDMI, USB, AV, RGB, Component		
Native Resolution	3840×2160 (UHD)		
Brightness	400cd/m2		
Orientation	Portrait and Landscape		
Contrast Ratio	1200:1		
Width/Height/Depth Including Monitor	45.12" x 26.14" x 3.07"	59.06" x 33.98" x 3.03"	71.26" x 41.02" x 3.11"
Weight Including Monitor	57.98 lbs	104.50 lbs	175.27 lbs
OS Support	Windows, Google Chrome, Android, Mac, Linux		



Phone: 802-874-0123 Fax: 703-991-8770 Email: sales@tsitouch.com

tsitouch.com