

Phone: 802-874-0123 Fax: 703-991-8770

Email: sales@tsitouch.com

tsitouch.com

LG UHD Infrared Touch Screen Solutions



Infrared Interactive Solution

The TSItouch solution is Infrared (IR) based, allowing for a high accuracy interactive experience. The usage of IR technology allows for virtually any input to be detected (pen/stylus, user's fingers, palms, gloved fingers). The TSItouch overlay is a full steel chassis integrated with tempered cover glass, which increases durability and optical clarity, while protecting the display.



Multi-Touch Screen True multi-touch support for all major operating systems. 6, 10, 12, or 32 simultaneous touch point options are available



Ultra-Fast Response Time

Allows for split second reactions between touch point and screen. Rapid and smooth touch response



Superior Design

Full steel chassis combined with tempered glass provides additional protection to the LCD panel



Branding Free

Branding/logo free, not to divert attention from your brand and messaging



24/7 Commercial Grade Display Commercial grade display

Commercial grade displiwith around the clock functionality



Easy Integration

Unrivaled simplicity makes installation easier and faster



HID Compliant

Maximum compatibly with numerous operating systems, plug-and-play





Customizable


Custom colors silk screening, and logos available



Solution Sizes Available







| Specification | 49" | 65" | 79" |
|---|---|-----------------------------------|-------------------------|
| Display Compatible | 49UX340C | 65UX340C | 79UX340C |
| Part Number | TSI49PLBWQ6ARZZ | TSI65PLCSQ6ARZZ | TSI79PLLMQ6ARZZ |
| Protective Glass | 1/8" Anti-Reflective Cover Glass | 3/16" Anti-Reflective Cover Glass | |
| Viewing Angle | 178x178 degrees | | |
| Audio Output | 10W + 10W | | |
| Touch Technology | IR G5 | | |
| Touch Points | 6 Point | | |
| Response Time | 9ms | | |
| Touch Accuracy | +/- 1.5mm (Over 99% Area) | | |
| Interface | Type A USB | | |
| Communication | USB 2.0 | | |
| Power Supply Mode | Single USB connection (5v, 1A) | | |
| Duty Cycle | 24/7 | | |
| Panel Technology | IPS | | |
| Aspect Ratio | 16:9 | | |
| Connectivity | (2) HDMI, USB, AV, RGB, Component | | |
| Native Resolution | 3840x2160 (UHD) | | |
| Brightness | 400cd/m2 | | |
| Orientation | Portrait and Landscape | | |
| Contrast Ratio | 1200:1 | | |
| Width/Height/Depth Including Monitor | 45.12" x 26.14" x 3.07" | 59.06" x 33.98" x 3.03" | 71.26" x 41.02" x 3.11" |
| Weight Including Monitor | 57.98 lbs | 104.50 lbs | 175.27 lbs |
| OS Support | Windows, Google Chrome, Android, Mac, Linux | | |



Phone: 802-874-0123 Fax: 703-991-8770 Email: sales@tsitouch.com

tsitouch.com