



INFRARED TOUCH SOLUTION

75" Integrated Touchscreen Display


TSI Touch's Infrared (IR) solution for LG®'s 75" UL3J-E Series monitors allows for a highly accurate touchscreen experience. Through the use of Infrared technology, virtually any input can be detected (pen/stylus, user's fingers, palms, gloved fingers).

Our all-metal bezel construction, combined with high strength glass, adds considerable protection to the display, while also keeping your content crisp and bright.



SPECIFICATION	DETAIL	
<i>Product Name</i>	Touchscreen only	75UL3J-E with Integrated Touchscreen
<i>Part Number</i>	TSI75NL14TACGZZ	TSI75PLYGTACGZZ
<i>Touchscreen Type</i>	Infrared on Anti-Glare Glass	
<i>Number of Touch Points</i>	10 points simultaneous touch	
<i>Touchscreen Interface</i>	USB 2.0 Type A Male connector with 57" cable	
<i>Touchscreen Power</i>	USB 5VDC Maximum 1.5W	
<i>Touch Response Time</i>	≤8ms	
<i>Touch Accuracy</i>	+- 1mm	
<i>Minimum Touch Object Size</i>	6mm	
<i>Orientation Compatibility</i>	Landscape, Portrait	
<i>Brightness (w/touchscreen)</i>	N/A	290 nit
<i>Brightness (w/o touchscreen)</i>	N/A	330 nit
<i>Display Resolution</i>	3840 x 2160	
<i>Contrast Ratio</i>	1,200:1	
<i>Viewing Angle</i>	178/178	

Aspect Ratio	16:9
Video Inputs	HDMI (3, HDCP 2.2 / 1.4), USB 2.0 Type A (2)
Audio Output	Stereo Mini Jack
Operating System Compatability	Microsoft® Windows®, LG® SoC, Google® Chrome®, Android®, MacOS® , and many popular Linux® Distributions - <i>HID Compliant Compatability</i>
Display Power Supply	AC 100 - 240 V, 50/60 Hz
Display Power Consumption	Typical: 155 Watts/Max: 220 Watts
Operating Temperature	0°~40° C
Humidity	10~80% Non-condensing
Integrated Dimensions (W x H x D)	67.95" x 39.65" x 3.12"
Viewable Area	65.0" x 36.61"
Integrated Display Weight	135.6 lbs.
Packaged Weight	193.6 lbs.
VESA Pattern	400 x 400 mm
Recommended Duty Cycle	16/7
Service and Support	3 Year Repair & Return Warranty
In the Box	Integrated Touchscreen Display, Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries



For more information, please visit
www.tsitouch.com,
 email sales@tsitouch.com,
 or call 802-874-0123

Specifications and designs are subject to change without notice. Packaged weights are approximate.