



SMALL FORMAT SERIES

21.5", 23.8", and 27" PCAP Touchscreen Displays

TSI Touch's Projective Capacitive (PCAP) Small Format Displays allow for a highly accurate and secure interactive experience. These displays are engineered specifically for customers seeking a touchscreen display designed for the rigors of commercial use without having to sacrifice image quality or aesthetics. The product can easily be wiped clean, making it both a sleek and sanitary design.

Key Features:

- Compliant with the Trade Agreement Act (TAA)
- Industrial grade display designed for high-traffic and public spaces
- Products are engineered for long lifecycles (3+ years)
- All displays are backed by a three-year warranty from TSI Touch



SPECIFICATION	DETAIL		
Screen Size	21.5"	23.8"	27"
Part Number	TSI21PDAAVAZZZZ	TSI24PDABVAZZZZ	TSI27PDADVAZZZZ
Display Resolution	1920x1080	1920x1080	1920x1080
Display Area (mm)	476.06 x 267.79	527.04 x 296.46	597.6 x 336.1
Pixel Pitch (mm)	0.247 x 0.247	0.274 x 0.274	0.311 x 0.311
Viewing Angle	178/178	178/178	178/178
Response Time (ms)	22 (On/Off)	16 (On/Off)	12 (On/Off)
Brightness	250 nit	250 nit	300 nit
Contrast Ratio	1,000:1	3000:1	3000: 1
Color Depth	8 bit	8 bit	8 bit
Orientation Compatibility	Landscape/Portrait/Flat	Landscape/Portrait/Flat	Landscape/Portrait/Flat
DP	DP1.2 (1)	DP1.2 (1)	DP1.2 (1)
VGA	D-Sub15 (1)	D-Sub15 (1)	D-Sub15 (1)
HMDI	HDMI 1.4 (1)	HDMI 1.4 (1)	HDMI 1.4 (1)
USB Hub	USB Type A (2)	USB Type A (2)	N/A
Audio	3.5mm - In (1)/Out (1)	3.5mm - In (1)/Out (1)	3.5mm - In (1)/Out (1)
Touchscreen Type	Projected Capacitive	Projected Capacitive	Projected Capacitive
Touch Points	10 Point	10 Point	10 Point
Screen Printing	Black	Black	Black
Glass Coating	Anti-Glare	Anti-Glare	Clear
Interface	USB	USB	Combo(USB/RS232)
Color Temperature	Neutral/Warm/Cool/User	Neutral/Warm/Cool/User	Neutral/Warm/Cool/User

<i>OSD Languages</i>	English/French/German/ Italian/Polish/Spanish/ Dutch/Czech/Russian/ Japanese/Simplified Chinese	English/French/German/ Italian/Polish/Spanish/ Dutch/Czech/Russian/ Japanese/Simplified Chinese	English/French/German/ Italian/Spanish/Japanese
<i>Scaling Mode</i>	Full Screen/Aspect Ratio	Full Screen/Aspect Ratio	Full/5:4/4:3/16:9/1:1
<i>Speaker</i>	2W Speaker	2W Speaker	2W Speaker
<i>Convenience</i>	Kensington-lock™ prepared	Kensington-lock™ prepared	Kensington-lock™ prepared
<i>Additional Features</i>	ECO Mode/Blue Light Reducer	ECO Mode/Blue Light Reducer	N/A
<i>Power Supply</i>	AC 100~240V	AC 100~240V	DC 12V
<i>Power Consumption (W)</i>	35 (Max)	35 (Max)	40 (Max)
<i>Dimensions (mm)</i>	537 x 387 x 175 (with Stand) 537 x 339 x 69 (w/o Stand)	581 x 400 x 175 (with Stand) 581 x 360 x 69 (w/o Stand)	651 x 441x175 (with Stand) 651 x 402 x 69 (w/o Stand)
<i>VESA Mounting (mm)</i>	100 x 100	100 x 100	100 x 100
<i>Weight (kg)</i>	8.2 (with Stand) 6.5 (w/o Stand)	9.5 (with Stand) 7.7 (w/o Stand)	10.3 (with Stand) 8.4 (w/o Stand)
<i>Enclosure Color</i>	Black	Black	Black
<i>Front Face Design</i>	Sealed Front Face	Sealed Front Face	Sealed Front Face
<i>Tilt Range</i>	0°~+30°	0°~+30°	0°~+30°
<i>Operating Temperature</i>	10° - 40° C	10° - 40° C	10° - 40° C
<i>Operating Humidity</i>	30% - 75%	30% - 75%	30% - 75%
<i>Storage Temperature</i>	-20° - 60° C	-20° - 60° C	-20° - 60° C
<i>Storage Humidity</i>	10% - 90%	10% - 90%	10% - 90%
<i>Certifications and Compliances</i>	cULus(UL 62368-1;CAN/CSA-C22.2 62368-1-14), CB(IEC 62368-1), CE(EN55032;EN55035;EN 62368- 1),FCC Part 15,ROHS,WEEE	cULus(UL 62368-1;CAN/CSA-C22.2 62368-1-14), CB(IEC 62368-1), CE(EN55032;EN55035;EN 62368- 1),FCC Part 15,ROHS,WEEE	cTUVus(UL 62368-1;CAN/ CSA-C22.2 62368-1),CB(IEC 62368- 1),CE (EN55032; EN55024;EN 62368-1),FCC Part 15,ROHS, WEEE



For more information, please visit
www.tsitouch.com,
email sales@tsitouch.com,
or call 802-874-0123

Specifications are subject
to change without notice.

2/24/2023 v. 1.3